US006437902B2

(12) **United States Patent**
Daneman et al.

(10) **Patent No.: US 6,437,902 B2**
(45) **Date of Patent: Aug. 20, 2002**

(54) **OPTICAL BEAM STEERING SWITCHING SYSTEM**

(75) Inventors: **Michael J. Daneman**, Pacifica; **Behrang Behin**; **Satinderpall S. Pannu**, both of Berkley, all of CA (US)

(73) Assignee: **Onix Microsystems**, Richmond, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/917,431**

(22) Filed: **Jul. 28, 2001**

Related U.S. Application Data

(62) Division of application No. 09/536,164, filed on Mar. 25, 2000.

(60) Provisional application No. 60/191,987, filed on Mar. 24, 2000, provisional application No. 60/191,856, filed on Mar. 24, 2000, and provisional application No. 60/192,097, filed on Mar. 24, 2000.

(51) **Int. Cl.**[7] **G02B 26/00**; G02B 27/10

(52) **U.S. Cl.** **359/290**; 359/627

(58) **Field of Search** 359/290, 291, 359/296, 627

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,334,437 A		6/1982	Hunter	330/4.3
4,761,543 A		8/1988	Hayden	235/457
5,872,880 A		2/1999	Maynard	385/88
6,042,240 A		3/2000	Strieber	359/851
6,084,714 A	*	7/2000	Ushiyama et al.	359/627
6,330,102 B1		12/2001	Daneman et al.	359/290

FOREIGN PATENT DOCUMENTS

DE	296118818	12/1996	G02B/6/35
DE	19757181 A	7/1997	G02B/6/35
DE	19644918.9	4/1998	G02B/6/35

* cited by examiner

Primary Examiner—Ricky Mack
(74) *Attorney, Agent, or Firm*—Joshua D. Isenberg; JDI Patent

(57) **ABSTRACT**

A beam steering module and switching system. The steering module is composed of a N×M array of single axis mirrors able to rotate about a particular axis (X-axis), a second N×M array of single axis mirrors able to rotate about an axis orthogonal to that of the first N×M array of mirrors (Y-axis), and a relay lens designed to image the first mirror array onto the second mirror array such that the beam angle may be controlled in both the X and Y-axis by adjusting the angle of the appropriate mirrors in the X and Y mirror arrays. Two steering modules may be combined to form a switching system. With two such steering modules, it is possible to completely determine, at the plane of the output fiber array, the position and angle of an optical beam emerging from any of the input fibers.

13 Claims, 4 Drawing Sheets